


# phyCORE<sup>®</sup> i.MX 8 System on Module Series



phyCORE-i.MX 8M SOM

## phyCORE-i.MX 8M

**Optimized low-power and fan-less operation with 20 channel 32-bit 384KHz audio and 4Kp60 HDR video streaming capabilities:**

- // NXP i.MX 8M Quad / i.MX 8M Dual / i.MX 8M QuadLite
- // 32/64-bit ARM Cortex-A53/M4F, GC7000Lite GPU
- // **Applications:** HMI, 4K UltraHD Video Streaming, Handheld/Mobile, High Fidelity Audio Devices
- // DSD512 Audio Capability
- // 2.4/5 GHz WiFi / BLE 4.2 on board (U.FL antenna)
- // Low profile no-connector LGA footprint
- // eMMC or SLC NAND
- // Dimensions: 55 mm x 40 mm

## phyCORE-i.MX 8

**Ultimate in processing power and advanced virtualization, SafeAssure<sup>®</sup> Display, advanced vision and speech recognition:**

- // NXP i.MX 8Quad / i.MX 8DualPlus / i.MX 8DualMax
- // 32/64-bit ARM Cortex-A53/A72/M4F, Tensilica<sup>®</sup> HiFi 4 DSP, Dual GC7000XSVX
- // **Applications:** eCockpit, Navigation, High-end Infotainment, Robotics, Advanced Vision and Image Processing
- // Vulkan, OpenCL 2.0, OpenVX, and OpenGL 3.1 support
- // Dimensions: 73 mm x 45 mm



phyCORE-i.MX 8 SOM






phyCORE-i.MX 8X SOM

## phyCORE-i.MX 8X

**Scalable, Secure and Economical for safety certifiable applications:**

- // NXP i.MX 8QuadXPlus / i.MX 8DualXPlus / i.MX 8DualX
- // ARM Cortex-A35/M4F, Tensilica<sup>®</sup> HiFi 4 DSP, GC7000Lite
- // **Applications:** Industrial automation and control, Safety critical HMI, robotics, automotive/avionic displays, Industry 4.0, Patient Monitoring
- // SafeAssure<sup>®</sup> Display failover DSI, LVDS, and Parallel Display
- // High Assurance Boot
- // eMMC or SLC NAND
- // Dimensions: 52 mm x 42 mm

# phyCORE-i.MX 8 SOM Series Feature Overview:



|                                       | phyCORE-i.MX 8M                                    | phyCORE-i.MX 8                                  | phyCORE-i.MX 8M                                 |
|---------------------------------------|--|---|---|
| <b>Processor</b>                      | NXP i.MX 8M Quad / i.MX 8M Dual / i.MX 8M QuadLite | NXP i.MX 8Quad / i.MX 8DualPlus / i.MX 8DualMax | NXP i.MX 8Quad / i.MX 8DualPlus / i.MX 8DualMax |
| <b>Architecture</b>                   | ARM Cortex-A53/M4F                                 | ARM Cortex A53/A72/M4F                          | ARM Cortex A35/M4F                              |
| <b>DSP, GPU</b>                       | GC7000Lite GPU                                     | Tensilica HiFi 4 DSP, Dual GC7000XSVX GPU       | Tensilica HiFi 4 DSP, GC7000Lite                |
| <b>Memory / Storage</b>               |  |   |   |
| <b>RAM</b>                            | 4 GB MAX LPDDR4 RAM                                | 8 GB MAX LPDDR4 RAM                             | 4 GB MAX LPDDR4 RAM                             |
| <b>NOR Flash</b>                      | -  | 64 MB - 256 MB Octal SPI/DualSPI Flash          | 64 MB - 256 MB Octal SPI/DualSPI Flash          |
| <b>NAND Flash</b>                     | 128 MB - 1 GB (w/o eMMC)                           | -   | 128 MB - 1 GB (w/o eMMC)                        |
| <b>eMMC</b>                           | 4 GB - 128 GB (w/o NAND Flash)                     | 4 GB - 128 GB                                   | 4 GB - 128 GB (w/o NAND Flash)                  |
| <b>Serial Interfaces</b>              |  |   |   |
| <b>CAN</b>                            | -  | 2   | 3   |
| <b>USB</b>                            | 2x 3.0   | 1x 3.0, 1x 2.0 OTG                              | 1x 3.0, 1x 2.0 OTG                              |
| <b>Ethernet</b>                       | 1 10/100/1000                                      | 2 10/100/1000                                   | 2 10/100/1000                                   |
| <b>PCIe</b>                           | 1  | 2   | 1   |
| <b>Multimedia/ Display</b>            |  |   |   |
| <b>Display</b>                        | HDMI Out, 1x DSI                                   | 2x LVDS, HDMI In/Out, 2x DSI                    | 2x LVDS, 2x DSI, Parallel                       |
| <b>Camera</b>                         | 2x CSI   | 2x CSI  | 1x CSI, Parallel                                |
| <b>Graphics / Vision Acceleration</b> | OpenGL/ES 3.1, Vulkan, OpenCL 1.2                  | OpenVX, OpenGL/ES 3.1, Vulkan, OpenCL 2.0       | OpenGL/ES 3.1, Vulkan, OpenCL 1.2 EP            |
| <b>Video Decode</b>                   | 4Kp60 HDR (h.265, VP9), 4Kp30 (h.264, VP8)         | 4K h.264/h.265                                  | 4K (h.265), 1080p60 (h.264,VP8)                 |
| <b>Video Encode</b>                   | 1080p30 (h.264)                                    | 1080p30 (h.264)                                 | 1080p30 (h.264)                                 |
| <b>Audio</b>                          | 32-bit 384 KHz                                     | 24-bit 192 KHz                                  | 24-bit 192 KHz                                  |
| <b>Mechanical</b>                     |  |   |   |
| <b>Dimensions</b>                     | 55 mm x 40 mm                                      | 73 mm x 45 mm                                   | 52 mm x 42 mm                                   |
| <b>Connector</b>                      | LGA (400 pins)                                     | Samtec 0.5 mm pitch (480 pins)                  | Samtec 0.5 mm pitch (280 pins)                  |
| <b>Supply</b>                         | 3.3 V  | 3.3 V   | 3.3 V   |
| <b>Temperature</b>                    | -40°C to +85°C                                     | -40°C to +85°C                                  | -40°C to +85°C                                  |
| <b>Software</b>                       | Linux, Android                                     | Linux, Android                                  | Linux, Android                                  |
| <b>Availability</b>                   | Preliminary  | Limited Samples                                 | Preliminary                                     |



## SERVICES

Product developers with aggressive timelines or limited resources can employ PHYTEC's full range of design services, which include systems integration support with printed circuit board and software design services, Linux and Android expertise, and in-house manufacturing facilities.